# DROID LED - model: 815LED

# LED Low Voltage Track Luminaire



	Fixture Ty
	Catalog N
5	Project:
	Location:
25	

Fixture Type:	
Catalog Number:	
Project:	
l a antinu :	

### **PRODUCT DESCRIPTION**

Energy efficient track head using a pre-installed MR16 LED lamp. Fixture is specifically designed to ensure proper lamp fit. For use with WAC Lighting's 120V Track system and compatible with other manufacturer's track (consult factory for specific brands).

#### FEATURES

- 350° horizontal rotation and 90° vertical aiming
- "L" style yoke and pivoting head for easy adjustment
- Silicon hot aiming sleeve
- 34° beam spread

#### **SPECIFICATIONS**

Construction: Die-cast aluminum. Clear 1/8" tempered glass lens included. Heat resistant rubber grip over rear socket assembly.

Transformer: Soft start electronic transformer designed to prolong lamp life, with auto reset and short circuit protection. Input voltage: 120VAC/60Hz. 1W minimum load.

Lamp: 12V MR16 LED (included).

Dimming: Dims to 1% with electronic low voltage (ELV) dimmer.

Finish

PT/BK

PT/WT

BK

wт

Finish: Powder coat paint in Black (BK), Platinum track head w/Black adapter (PT/BK), Platinum track head w/White adapter (PT/WT) and White (WT). Black and Platinum fixtures include black LED lamp, White fixture includes white LED lamp.

Black

White

Platinum/Black

Platinum/White

Standards: UL & CUL Listed.

**ORDER NUMBER** 

HHT H Track

JHT J Track

L Track

System

I HT

## FINISHES



Example: LHT-815LED-WT

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585

815LED

Model #

815LED

Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 S Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

• "Quick-Ship" item: always in stock and ready for immediate shipment • 25,000 hour rated life

5 year WAC Lighting product warranty

#### **FIXTURE PERFORMANCE**

Color Temp	Watt	Lumens	Efficacy	CBCP	CRI	
3000K	6.4	360	56.3 Lm/W	850	81	

w

3.7

4.9

6.1

7.3

#### LAMP PERFORMANCE

Distance

6 ft

8 ft

10 ft

12 ft

0° Aiming Angle (ceiling to floor)

FC

24

13

9

6

L

3.7

4.9

6.1

7.3

45° Aiming Angle (ceiling to wall)

FC	L	w
8	8.1	5.2
5	10.8	6.9
3	13.5	8.6
2	16.2	10.4