TELESCOPING NECK - model: DL-188


Line Voltage Clamp Mount Spot Light

WAC LIGHTING

Responsible Lighting®



Fixture Type:	
Catalog Number:	
Project:	
Location:	



PRODUCT DESCRIPTION

Line voltage display light for use on wall partitions, display booths, and portable work areas. Can utilize a variety of medium base lamps up to 150W. Mounts to flat surfaces with tension clamp, accomodating widths of $\frac{1}{2}$ " to $\frac{2}{2}$ ".

FEATURES

- Includes 2" clamp and 10' cord.
- Sliding adjustable socket to accommodate lamp positioning
- Accepts various lamp options (order separately) LED Lamps: LED PAR20, LED PAR30, LED BR20, LED BR30, LED BR40 Non-LED Options (120V, 150W max): BR30, PAR20, PAR30, PAR38
- Periscoping style arm can allow the head of the display light to be place up to an extra 10" back from surface and then locked in place with a simple twist and lock.

SPECIFICATIONS

Aiming: Yoke and swivel aiming feature allows a full range of vertical and horizontal orientation. Large locking screw assures the aiming angle is kept in place through continuous use and maintenance.

Materials: Fixture head and connector are aluminum. Periscoping arm is steel. Clamp is heavy duty polycarbonate. Bi-pin socket is ceramic with silver plated contacts.

Standards: ETL and cETL Listed.

ORDER NUMBER

Model # Finish BK Black DL-188 WT White

DL-188

Example: DL-188-WT

LED LAMPS (optional)

Model #	Finish	
PAR20LED-10N30 PAR30LED-L14N30 PAR38LED-17N30	BK WT	Black White
BR20LED-7N27 BR30LED-11N27 BR40LED-15N27	wT	White

Example: PAR30LED-L14N30-WT

ALTERNATIVE CLAMPS (optional)

Model # Description Finish Pipe Clamp - For pipes 1/2" to 21/2" **BK** Black 4" Clamp - For flat surfaces from 2" to 4" wide WT White Example: DLC-P-WT

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center 615 South Street • Garden City, NY 11530 Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 168 Brea Canyon Road • City of Industry, CA 91789 Phone (800) 526.2588 • Fax (800) 526.2585