


HR-3LED-H18-HICA

3.5" Tesla™ New Construction Housing
277V – IC-Rated – Airtight

WAC LIGHTING
Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

IC-Rated, airtight new construction housing.
For use with HR-3LED series trims.

FEATURES

- Cutout: 4 $\frac{5}{8}$ "
- 277V AC 50/60Hz input
- IC-Rated
- Airtight
- Provided with push-in wire connector for easy installation
- Accommodates ceiling thickness from $\frac{1}{2}$ "- $\frac{3}{4}$ "
- UL and CUL Listed
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Housing and junction box are 20 gauge steel.
Frame and hanger bars are heavy gauge galvanized steel.

J-Box: Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

Driver: Electronic driver, 277VAC 50/60Hz input, 21.5W output. Power factor >0.9. Not dimmable.

Mounting: Supplied with hanger bars, adjustable from 1 $\frac{1}{2}$ "-2 $\frac{1}{2}$ " to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. Accommodates surfaces from $\frac{1}{2}$ "- $\frac{3}{4}$ " thick. 4 $\frac{5}{8}$ " cutout hole.

Rating: IC-Rated: Suitable for direct contact with insulation.

Standards: UL & CUL Listed. Airtight: meets ASTM standard E283-04 under California 2005 Building Energy Efficient Standards and WAC 50-11-0502 of the State of Washington.

ORDER NUMBER

HR-3LED-H18-HICA

COMPATIBLE TRIMS

Model #	Description	Beam	Color Temp	Finish
HR-3LED-ET118*	Round, Open Reflector Downlight Energy Star	40° (F)	2700K (27), 3000K (W) 3500K (35), 4000K (C)	Brushed Nickel (BN) Copper Bronze (CB) White (WT)
HR-3LED-T218	Round, Shower Light	28° (N)		
HR-3LED-T418	Round, 30°-45° Adjustable	15° (S), 28° (N), 50° (F)		
HR-3LED-T518N	Square, Wall Wash	N/A		
HR-3LED-T618	Round, 0°-30° Adjustable Pinhole	15° (S)		
HR-3LED-T718	Square, Open Reflector Downlight	15° (S), 28° (N), 50° (F)		
HR-3LED-T818	Square Shower Light (Wet Listed)	28° (N)		
HR-3LED-T918	Square 30°-45° Adjustable	15° (S), 28° (N), 50° (F)		
HR-3LED-T118 HR-3LED-T318	Round, Open Reflector Downlight Round, 0°-30° Adjustable	15° (S), 28° (N), 50° (F)	2700K (27), 3000K (W) 3500K (35), 4000K (C)	Haze/White (HZ/WT) Haze/Brushed Nickel (HZ/BN) Haze/Copper Bronze (HZ/CB) Specular Black/White (SB/WT) Specular Black/Brushed Nickel (SB/BN) Specular Black/Copper Bronze (SB/CB) Brushed Nickel (BN), Copper Bronze (CB), White (WT)

Example: HR-3LED-T118F-W-HZ/WT

See individual trim spec sheets for complete information.

*NOT Energy Star rated when using 277V housing.

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585