INVISIBLE TRIM REMODEL HOUSING WACLIGHTING

2" Volta

SPECIFICATIONS

Input:	Universal 120 - 277V AC 50/60 Hz
Standards:	ETL & cETL
Dimming:	Electronic Low Voltage (ELV): 100%-5% 0-10V: 100%-0%
Mounting:	Ceiling thickness: ½ - 1" Ceilingcut out (Round): Ø 4 ¼" Ceiling cut out (Square): 4 ¼" x 4 ¼"
Construction:	20 Gauge cold rolled steel Diecast spackle flange included
Warranty	5 year WAC Lighting product warranty

Responsible Lighting®

Standarder					Fixt	ture Type:			
Standards:	ETL & cETL								
Dimming:	Electronic Low Voltage (ELV): 100%-5% 0-10V: 100%-0%				Cat	Catalog Number:			
Mounting:	Ceiling thickness: ½ - 1" Ceilingcut out (Round): Ø 4 ¼" Ceiling cut out (Square): 4 ¼" x 4 ¼"				Pro	Project:			
Construction:	n: 20 Gauge cold rolled steel Diecast spackle flange included					Location:			
Warranty	5 year WAC Lighting	g product warranty							
Round Re	emodel				Squa	are Remodel			
(366	C		C	9	50		•
2 ^{15/6}					2 ¹⁵ / ₁₆ "				5 ³ / ₄ "
HOUSING	i (Required)	Model R2RR	Trim Type	Power		INVISIBLE T	RIM™ INSTALLATION	L Ceiling Thio	ckness
Non-IC		Round	L Invisible	15 15W	Non-IC	Trim Model	Trim Description	1/2"	1"
R2	L-	R2SR Square	Trim	22 22W	Non-IC	R2RD2T R2SD2T	Downlight	Yes	Yes
Example: R2RRL-15						R2RD1T R2SD1T	Shallow Regressed Downlight	Yes	Yes
Drywall Ceiling (by others)						R2RAT R2SAT R2RPT R2SPT	Adjustable/Pinhole	Yes, to 45°	Yes, to 35°
Spackle	(by others) Die-	Invisible Trim Spac	Thickness			R2RWT R2SWT	Wall Wash	Yes	Yes
waclighting.co Phone (800) 52 Fax (800) 52	.2588 44 Harbor Park Drive			Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122		Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760			

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JAN 2019