Model: WL-LED101

LEDme® Step Light



Responsible Lighting®



Fixture Type: Catalog Number: Project: Location:


PRODUCT DESCRIPTION


Horizontal rectangle LEDme® Step Light with Anti-microbial powder coat paint proven to restrain a wide range of bacteria, coliform, mold, fungus, algae, and yeast. Designed for safety and style on stairways, patios, decks, balcony areas, walkways and building perimeters.


Features an architectural design. Energy efficient for long-lasting indoor and outdoor lighting solutions. Creates an attractive, romantic impression at night.

FEATURES

- Direct wiring, no driver needed
- Low profile, flush to wall aesthetics with no visible hardware
- 54,000 hour rated life
- Balanced lighting, free of shadows with minimum glare
- Up to 200 fixtures can be connected in parallel
- 5 year WAC Lighting product warranty







SPECIFICATIONS

Construction: Die-cast aluminum

Power: Direct wiring, no remote driver needed.

Input: 120V 50/60Hz (277V special order/3000K, Amber (AM)

Light Source: HV-AC High Power LED, CRI: 90

Optional color lenses. Total power consumption of 3.5W

Mounting: Fits into $2'' \times 4''$ J-Box with minimum inside dimensions of

 $3"L \times 2"W \times 2"H$

Includes bracket for J-Box mount.

Dimming: Dim to 10% with ELV dimmer (120V only).

Approved dimmers: Lutron Nova-T NTELV-300 & NTELV-600.

Lutron Vietri VTELV-600, Lutron Diva DVELV-300P, Lutron Skylark SELV-300P, Lutron Maestro MAELV-600

Standards: IP66, UL & cUL Listed for wet locations, Title 24 Compliant (120V only)

ORDER NUMBER

Model #		Light Color			Finish	
WL-LED101	120V	27 30 AM	2700K 3000K Amber (610nn	wt	White	
WL-LED	101	-[- WT	1		

Example: WL-LED101-27-WT

For 277V, add "F" before CCT: WL-LED101F-30-WT