


615 South Street Garden City, NY 11530 Tel:516-515-5000 Fax:516-515-5050 www.waclighting.com

CATALOG NUMBER	<u>TYPE</u>
PROJECT	

FLUORESCENT PENDANT SOCKET

MODEL L,H,JTK-F1













Pendant Ordering Matrix	
Model Number	Finishes
LTK-F1	DB= Dark Bronze, Cord=Black
HTK-F1	DB= Dark Bronze, Cord=Black
JTK-F1	DB= Dark Bronze, Cord=Black

Ordering Example (model number-finishes): JTK-F1-DB

	D	
1110-1	Detai	ıc
UUL		

The LTK-F1 fixture used for WAC L system track. The HTK-F1 **Description:**

> fixture used for WAC H system track. The JTK-F1 fixture used for WAC J system track. Fluorescent pendant socket for use with

selected shades (See matrix below).

Track adaptor is polycarbonate. Materials:

Die-cast aluminum and plated socket housing.

Three pin supports may be detached to allow additional shade

styles.

Lamping: Uses one 120V GU24 self-ballasted compact fluorescent lamp in 26

Watts maximum. (13w 2700K Included).

Finish: DB - Dark Bronze

U.L & C.U.L Listed. Energy Star Recognized. Listing:

Specification Features

- Glass shade is ordered as a separate line item and installed in the field .Compatible shades are shown on page 2, eleven distinct shade choices.
- 6' long socket set cable allows easy filed cutting to desired drop length.
- Energy saving fixture and lamp life lasting more than 8000 hours for including lamp.
- 5 year product warranty and 2 years included lamp warranty.



CATALOG NUMBER	<u>TYPE</u>
PROJECT	

FLUORESCENT PENDANT SOCKET

MODEL L, H, JTK-F1

Pendant Ordering Matrix	
Shade	Finishes
See table blow	See table blow

PLD-G421GR	67/8"	PLD-G426AM	77/8	PLD-G424WT	6 7/8"
PLD-G423PR	11 5/8"	PLD-G472WT	71/2*	PLD-G486WT	6.3/4"
PLD-G471WT	8	PLD-G474WT	81/2	PLD-G487AM	81/2"
PLD-G488WT	71/2*	PLD-G483IV	81/2*		

Finish Key: AM - Amber, GR - Green, PR - Purple, IV - Ivory, WT - White




615 South Street Garden Oity, NY 11530 Tel:516-515-5000 Fax:516-515-5050 www.waclighting.com

CATALOG NUMBER	<u>TYPE</u>
PROJECT	

FLUORESCENT PENDANT SOCKET

MODEL L,H,JTK-F2











Pendant Ordering Matrix

Model Number

ETK-F2

BN= Brushed Nickel, Cord=Grey

HTK-F2

BN= Brushed Nickel, Cord=Grey

JTK-F2

BN= Brushed Nickel, Cord=Grey

BN= Brushed Nickel, Cord=Grey

Ordering Example (model number-finishes): JTK-F2-BN

Prod	uct	Deta	ills

Description: The LTK-F2 fixture used for WAC L system track. The HTK-F2

fixture used for WAC H system track. The JTK-F2 fixture used for WAC J system track. Fluorescent pendant socket for use with

selected shades (See matrix below).

Materials: Track adaptor is polycarbonate.

Die-cast aluminum and plated socket housing.

Three pin supports may be detached to allow additional shade

styles.

Lamping: Uses one 120V GU24 self-ballasted compact fluorescent lamp in 26

Watts maximum. (13w 2700K Included).

Finish: BN= Brushed Nickel

Listing: U.L & C.U.L Listed. Energy Star Recognized.

Specification Features

- Glass shade is ordered as a separate line item and installed in the field .Compatible shades are shown on page 2, eleven distinct shade choices.
- 6' long socket set cable allows easy filed cutting to desired drop length.
- Energy saving fixture and lamp life lasting more than 8000 hours for including lamp.
- 5 year product warranty and 2 years included lamp warranty.



CATALOG NUMBER	<u>TYPE</u>
PROJECT	

FLUORESCENT PENDANT SOCKET

MODEL L, H, JTK-F2

Pendant Ordering Matrix	
Shade	Finishes
See table blow	See table blow

PLD-G421GR	67/8"	PLD-G426AM	7778	PLD-G424WT	6 7/8"
PLD-G423PR	11 5/8"	PLD-G472WT	91/4"	PLD-G486WT	6.3/4"
PLD-G471WT		PLD-G474WT	81/2"	PLD-G487AM	\$1/2"
PLD-G488WT	7 1/2*	PLD-G483IV	81/2		

Finish Key: AM - Amber , GR- Green, PR-Purple, IV-Ivory, WT - White